

SAFETY DATA SHEET

Comply with OSHA's
Occupational Safety and Health
Administration Standard, 29
CFR 1910.120. This
Standard must be
read in conjunction with
other applicable
regulatory and
company specific
requirements.

Hazard Rating

4-Extreme
3-High
2-Moderate
1-Slight
0-Insignificant

NFPA

Toxicity	3
Fire	0
Reactivity	2
Special	

MANUFACTURER: TERMINATER STK# 165A Date Revised 2/1/2002

Emergency Telephone Number
 1-800-535-5053 Infotrac

Telephone Number for Information
 1-303-289-6320

Blending Inc.
 (Number, Street, City, State, Zip Code)
 5 Fox Street. Unit B
 Denver Co 80216

Hazardous Ingredients/Identity Information

Chemical Identity; Common	OSHA PEL	ACGIH TLV	Other	%
CAS# 7664-93-3	3 ppm			17
CAS# 7664-93-9	1 ppm			10

Physical/Chemical Characteristics

Specific Gravity (Water=1):
NA

Melting Point:
NA

Evaporation Rate (Butyl Acetate=1):
NA

Solubility in Water:
Complete

Odor:
to Tan Liquid/Sharp odor

Fire and Explosion Hazard Data

Method Used):	Flammable Limits	LEL	UEL
Material does not exhibit a flash point.		NA	NA

Media:
 water, Carbon Dioxide, Foam

Testing Method:
 or positive pressure self-contained breathing apparatus.

Explosion Hazards:
 c emissions are possible in a fire situation. Not a fire or explosion hazard.

Reactivity Data

Conditions to avoid:

Materials to Avoid):
 ng alkalis, phosphorous pentoxide,
 ine

Compositions or Byproducts:

Normal decomposition on burning may produce toxic vapors.

Flammability:

Not Occur

Conditions to Avoid:

FLAMMABLE

STK#

Cont'd

Health Hazard Data

Exposure:	Inhalation? Yes	Skin? Yes	Ingestion? Yes
------------------	------------------------	------------------	-----------------------

Acute and Chronic):

Off skin. Eye: Moderately irritating on Draize test.

May cause burn. Inhalation: Causes severe irritation. Skin: May cause severe chemical burns

which may not be immediately apparent. Ingestion: May cause severe burns to the gastrointestinal

tract. Absorption of fluoride may cause death. May aggravate existing skin or respiratory ailments.

OSHA
Regulated?
Not Listed

Symptoms of Exposure:

Irritation, burning. May cause chemical burns on skin. Eye: Mildly irritation on Draize Test,

may cause burn. May cause severe burns to gastrointestinal tract.

Conditions Generally Aggravated by Exposure:

May aggravate existing skin or respiratory ailments.

First Aid Procedures:

Contact: immediately flush with plenty of water or normal saline for at least 15 minutes,

obtain immediate medical attention. Skin Contact: immediately rinse exposed area with water

for several minutes. Remove contaminated clothing. If immediate rinsing is not performed seek

immediate medical attention. Inhalation: remove to fresh air. For severe or prolonged high level exposure,

obtain immediate medical attention. Ingestion: Do not induce vomiting. Immediately administer by mouth any

available substance that contains calcium (Tums, milk) or magnesium (Maalox, Mylanta.)

DO NOT administer activated charcoal. Obtain immediate medical attention.

Precautions for Safe Handling and Use

What to do in case material is released or spilled:

Contain spill. Remove with inert absorbant material. Wash spill area with water.

Control method:

In accordance with Federal, State and local regulations.

Precautions to be taken in handling and storing:

Wash thoroughly after handling. Keep container closed when not in use. Store away from food and food

products.

Precautions:

Keep away from strong alkalis. Avoid contact with skin or any body parts or clothing that could absorb

product.

Personal Protective Equipment - Control Measures

Respiratory Protection (Specify Type):

Respirator required if adequate ventilation is maintained; otherwise, a NIOSH/MSHA approved organic vapor

respirator is advised.

Local Exhaust: Adequate

Hand Protection:

Gloves: Rubber or Neoprene

Approved Safety Glasses with side shields.

Clothing:

Wash and safety shower should be available.

Practices:

Do not get in eyes, on skin or on clothing. Use only with adequate ventilation.