

MATERIAL SAFETY DATA SHEET # 26-S



Date-Issued: 11/05/02
MSDS Ref. No: 26S
Date-Revised: 11/05/02
Revision No: New MSDS

Fast Spray

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Fast Spray
PRODUCT DESCRIPTION: Aerosol
PRODUCT CODE: 26-S
PRODUCT FORMULATION NAME: Fast Spray
GENERIC NAME: Aerosol

MANUFACTURER

Southwest Auto Care ®
Autocare™
17054 South 54th Street
Chandler, Arizona 85226-4118

24 HR. EMERGENCY TELEPHONE NUMBERS

INFOTRAC (U.S.): (800) 535-5053
Office Phone : (480) 705-0273
Emergency Phone: (888) 846-2442

COMMENTS: To the best of our knowledge, this Material Safety Data Sheet conforms to the requirements of US OSHA 29 CFR 1910.1200.

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS#</u>	<u>EINECS#</u>
Propane/Butane Blend	10 - 30	68476 -85-7	
Hexane	40 - 50	110 -54-3	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Danger: Extremely Flammable. Contents under pressure.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: May cause slight irritation.

INGESTION: Harmful if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Eye contact may cause redness, tearing and a burning sensation.

SKIN: Repeated or prolonged skin contact may cause redness and irritation.

INGESTION: Ingestion may cause nausea and irritation.

INHALATION: Prolonged inhalation of vapors may cause irritation to nasal and respiratory tract.

ACUTE TOXICITY: overexposure to vapors may cause headaches, dizziness, confusion and nausea,

CHRONIC: Not available

CARCINOGENICITY: Not available

REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: Not available

MEDICAL CONDITIONS AGGRAVATED: Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product.

ROUTES OF ENTRY: Include skin contact, skin absorption, eye contact, inhalation and ingestion

TARGET ORGAN STATEMENT: Not available

CANCER STATEMENT: Not available

PHYSICAL HAZARDS: Contents under pressure. Flammable liquid.

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Seek medical attention if irritation persists.

SKIN: Remove contaminated clothing. Wash with soap and water.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE LIMITS: 1.8% (Propellant) to 9.2% (Propellant)

FLAMMABLE CLASS: Extremely Flammable. Material will readily ignite at room temperatures.

GENERAL HAZARD: Flammable liquid. Keep away from heat and open flames.

EXTINGUISHING MEDIA: use foam, dry chemical or Co2 extinguisher

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide and Carbon Dioxide

EXPLOSION HAZARDS: Vapors may ignite explosively. Exposure to heat or prolonged exposure to sun may cause bursting

FIRE FIGHTING PROCEDURES: Water may be ineffective, but may be used to cool containers exposed to heat.

AUTOIGNITION TEMPERATURE: Not available

FLASHPOINT: Not available

SENSITIVE TO STATIC DISCHARGE: None expected

SENSITIVITY TO IMPACT: None expected

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Remove all ignition sources. Contain and collect with absorbent

LARGE SPILL: Remove all ignition sources. Shut off leak if safe to do so. Contain material to avoid run off and collect spill with absorbent.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of Children.

HANDLING: Do not puncture or incinerate.

STORAGE: Do not expose to heat or store at temperatures above 120 F.

SHELF LIFE: Two years

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

		<u>EXPOSURE LIMITS</u>					
		<u>OSHA PEL</u>		<u>ACGIH TLV</u>		<u>Supplier OEL</u>	
		<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>
Propane/Butane Blend	TWA	1000		1000			
Hexane	TWA	500	1800	500	1760		
	STEL			1000	3500		

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields or goggles.

SKIN: Use Nitrile/ Vinyl gloves

RESPIRATORY: NIOSH respirator -(organic vapor) in absence of proper environmental control.

PROTECTIVE CLOTHING: Clean, body-covering clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

10. STABILITY AND REACTIVITY

STABLE: YES

HAZARDOUS POLYMERIZATION: NO

CONDITIONS TO AVOID: Avoid high temperatures.

11. TOXICOLOGICAL INFORMATION

SENSITIZATION: Not available

TARGET ORGANS: Not available

SUBCHRONIC:

Not available

CARCINOGENICITY:

IARC: Listed by IARC- NO

NTP: Listed by NTP- NO

OSHA: Listed by OSHA- NO

MUTAGENICITY: Not available

REPRODUCTIVE EFFECTS: Not available

TERATOGENIC EFFECTS: Not available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Not available

ECOTOXICOLOGICAL INFORMATION: Not available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose in accordance with local, state, and federal laws.

EMPTY CONTAINER: Do not incinerate.


14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)
PROPER SHIPPING NAME: CONSUMER COMMODITY-ORM-D
TECHNICAL NAME: CONSUMER COMMODITY-ORM-D

15. REGULATORY INFORMATION

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



WHMIS Compressed Gas



WHMIS Toxic



WHMIS Flammable Aerosol

16. OTHER INFORMATION

PREPARED BY: Jim Kinzy

REVISION SUMMARY New MSDS

HMIS RATING

NFPA CODES

HEALTH:	1
FLAMMABILITY:	4
REACTIVITY:	0
PERSONAL PROTECTION:	I

MANUFACTURER DISCLAIMER: The information in this MSDS was obtained from current and reputable sources. However, the data is provided without any warranty, express or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.