

(MSDS)

ITEM NUMBER: 802 - SPRAYWAY CHEWING GUM REMOVER

VERSION 3 EFFECTIVE DATE: 03/14/01 SUPERCEDES DATE: 07/17/00 ORIGINAL PREPARER: Amanda M. Wlodarczyk

IDENTITY (As Used On Label and List): CHEWING GUM REMOVER

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (NFPA): Health = 1 , Fire = 4 , Reactivity = 1 , Protective Equipment = A

(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

SECTION I

SPRAYWAY INC.

TELEPHONE NUMBER FOR INFORMATION : 1-800-332-9000

484 VISTA AVE.

ADDISON

DATE PRINTED : 7/17/01 NAME OF PREPARER : Ron Cepa

IL 60101

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names	Exposure Limits (LD50-Oral Rat)	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
----------------	------------------------------------	---------------------------	------------------	-------------	----------

Liquified Gas Mixture	ND	No	-	-	70-80
Dimethyl ether (CAS# 115-10-6)	ND	--	NE	NE	-
Isobutane (CAS# 75-28-5)	ND	--	NE	NE	-
Propane (CAS# 74-98-6)	ND	--	NE	1000 ppm	-
1,1,1,2-Tetrafluoroethane (CAS#811-97-2)	ND		NO	NE	NE 20-30

Components Listed As A Suspected Carcinogen: None

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 158 @ 130F Specific Gravity (H2O=1): <1

Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1

Appearance and Odor: Clear, colorless, ethereal odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is to be labeled as flammable as described in 16CFR 1500.3 and 1500.45.

Flashpoint: <0F (Propellant); NA (Concentrate)

Flammable Limits - % Volume In Air (Propellant): (approx)LEL: 1.8 UEL: 18.0

Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA

Incompatibility (Materials to Avoid): Oxidizing agents Hazardous Decomposition Products:

